



MOWER SPECIFICATIONS

MZ MAGNUM MODEL

KOHLER 725cc

Kawasaki 726cc

Cutting Width	4800/48"; 5400/54"	4800/48"; 5400/54"
Cutting Height	1"–4.5" with Deck Height Control System	1.5"–4.5" with Deck Height Control System
Blades	4800/7/32" x 2 1/2" x 16 1/2", High Lift, Heat Treated 5400/7/32" x 2 1/2" x 18 1/2", High Lift, Heat Treated	4800/1/4" x 2 1/2" x 16 1/2", High Lift, Heat Treated 5400/1/4" x 2 1/2" x 18 3/4", High Lift, Heat Treated
Lift and Height Adjustment	Foot-Assist Lift	Foot-Assist Lift
Blade Belt	Single V-Belt Spring Tension	Single V-Belt Spring Tension
Anti-Scalp Rollers	4 Total (2 Front, 2 Rear)	4 Total (2 Front, 2 Rear)
Deck Flotation	Floats on (4) 1/4" Deck Hangers	Floats on (4) 1/4" Deck Hangers
Deck Thickness	3/16" Thick Solid Steel	3/16" Thick Solid Steel
ENGINE		
Gross Horsepower	725cc Air-Cooled Kohler Pro 7000	726cc Air-Cooled Kawasaki FR
Cylinders	90 Degree V-Twin	90 Degree V-Twin
Displacement	725 cc	725 cc
Maximum Torque	41.3 ft. lbs. @ 2400 RPM	41.3 ft. lbs. @ 2400 RPM
Fuel Requirement	Unleaded Gasoline (87 Octane or higher)	Unleaded Gasoline (87 Octane or higher)
Fuel Capacity	5 Gallons	5 Gallons
Fuel Filter	Replaceable Automotive Type	Replaceable Automotive Type
Cooling System	Air-Cooled	Air-Cooled
Ignition	Electronic	Electronic
Starter	12 Volt	12 Volt
Charging System	16 amp	16 amp
DRIVE SYSTEM		
Transmission	Dual Integrated Hydrostatic Transaxle	Dual Integrated Hydrostatic Transaxle
Pump Drive	Integrated Axial Piston Pump & Motor w/Gear Reduction	Integrated Axial Piston Pump & Motor w/Gear Reduction
Wheel Drive	Integrated with Gear Reduction	Integrated with Gear Reduction
Hydrostatic System Oil	20W50 Motor Oil	20W50 Motor Oil
Hydraulic Filter	—	—
Pumps (2)	EZT Integrated Unit	EZT Integrated Unit
Hydraulic Coolers (2)	7" Cooling Fan per Unit	7" Cooling Fan per Unit
Weight	4800/661 lbs. ; 5400/686 lbs.	4800/661 lbs. ; 5400/686 lbs.
Overall Height	42"	42"
Overall Width	4800/62"; 5400/67"	4800/62"; 5400/67"
Overall Length	76"	76"
Tire to Tire Width	46"	46"
Tires—Front	11 x 6.0-5 Smooth Tread	11 x 6.0-5 Smooth Tread
Tires—Rear	18 x 9.5-8 Turf Tread	18 x 9.5-8 Turf Tread
Steering	Dual Lever Steering, Independent Control	Dual Lever Steering, Independent Control
Turning Radius	Zero Degree, Turns Within Unit Length	Zero Degree, Turns Within Unit Length
Ground Speed (forward)	Up to 6 mph	Up to 6 mph
Parking Brake	External Cogg Brake	External Cogg Brake

SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at www.badboymowers.com. Not responsible for typographical errors. ©2017. Bad Boy, Inc., All Rights Reserved.