



MOWER SPECIFICATIONS

OUTLAW MODELS



Cutting Width	5400/54"; 6100/61"	5400/54"; 6100/61"
Cutting Height	1"–5" with Deck Height Control System	1"–5" with Deck Height Control System
Blades	5400/1/4" x 2 1/2" x 18 3/4", High Lift, Heat Treated 6100/1/4" x 2 1/2" x 21", High Lift, Heat Treated	5400/1/4" x 2 1/2" x 18 3/4", High Lift, Heat Treated 6100/1/4" x 2 1/2" x 21", High Lift, Heat Treated
Lift and Height Adjustment	Foot-Assist Manual Deck Lift	Foot-Assist Manual Deck Lift
Blade Belt	Single V-Belt Spring Tension	Single V-Belt Spring Tension
Anti-Scalp Rollers	6 Total (4 on the front, 2 on the rear)	6 Total (4 on the front, 2 on the rear)
Deck Flotation	Floats on (4) 1/4" Deck Hangers	Floats on (4) 1/4" Deck Hangers
Deck Thickness	1/4" Thick Solid Steel	1/4" Thick Solid Steel
ENGINE		
Gross Horsepower	810cc Vanguard	747cc Air-Cooled Kohler Confidant
Cylinders	90 Degree V-Twin	V-Twin
Displacement	810 cc	747 cc
Maximum Torque	42 ft. lbs. @ 2400 RPM	42.4 ft. lbs. @ 2600 RPM
Fuel Requirement	Unleaded Gasoline (87 Octane or higher)	Unleaded Gasoline (87 Octane or higher)
Fuel Capacity	13.8 Gallons	13.8 Gallons
Fuel Filter	Replaceable Automotive Type	Replaceable Automotive Type
Cooling System	Air-Cooled	Air-Cooled
Ignition	Electronic	Electronic
Starter	12 Volt	12 Volt
Charging System	20 amp	20 amp
DRIVE SYSTEM		
Transmission	Industrial Grade Dual Integrated Hydrostatic Transaxle	Industrial Grade Dual Integrated Hydrostatic Transaxle
Pump Drive	Integrated Axial Piston Pump & Motor w/Planetary Gear Reduction	Integrated Axial Piston Pump & Motor w/Planetary Gear Reduction
Wheel Drive	Hydro-Gear Integrated 4400 Series Transaxle	Hydro-Gear Integrated 4400 Series Transaxle
Hydrostatic System Oil	20W50 Motor Oil	20W50 Motor Oil
Hydraulic Filter	Internal, Replaceable. 1 per axle	Internal, Replaceable. 1 per axle
Pumps (2)	Hydro-Gear 12 cc Pump	Hydro-Gear 12 cc Pump
Hydraulic Coolers (2)	9" 3600 RPM Cooling Fan: One per Unit	9" 3600 RPM Cooling Fan: One per Unit
Weight	5400/1180 lbs /6100/1230 lbs.	5400/1180 lbs /6100/1230 lbs.
Overall Height	48"	48"
Overall Width	5400/62 1/2"; 6100/73 1/2"	5400/55 1/2" /6100/62 1/2"
Overall Length	86"	86"
Tire to Tire Width	5400/52" / 6100/56"	5400/52" / 6100/56"
Tires—Front	13 x 6.5–6 Smooth Tread	13 x 6.5–6 Smooth Tread
Tires—Rear	24x12-12 Turf Tread	24x12-12 Turf Tread
Steering	Dual Lever Steering, Independent Control	Dual Lever Steering, Independent Control
Turning Radius	Zero Degree, Turns Within Unit Length	Zero Degree, Turns Within Unit Length
Ground Speed (forward)	Up to 11 mph	Up to 11 mph
Parking Brake	Internal Wet Disk	Internal Wet Disk

ANOTHER MODEL ON NEXT PAGE

SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at www.badboymowers.com. Not responsible for typographical errors. ©2017. Bad Boy, Inc., All Rights Reserved.



MOWER SPECIFICATIONS

 **726cc**

Cutting Width	5400/54"; 6100/61"
Cutting Height	1"–5" with Deck Height Control System
Blades	5400/1/4" x 2 1/2" x 18 3/4", High Lift, Heat Treated 6100/1/4" x 2 1/2" x 21", High Lift, Heat Treated
Lift and Height Adjustment	Foot-Assist Manual Deck Lift
Blade Belt	Single V-Belt Spring Tension
Anti-Scalp Rollers	6 Total (4 on the front, 2 on the rear)
Deck Flotation	Floats on (4) 1/4" Deck Hangers
Deck Thickness	1/4" Thick Solid Steel
ENGINE	
Gross Horsepower	726 Air-Cooled Kawasaki FX
Cylinders	V-Twin
Displacement	725 cc
Maximum Torque	40 ft. lbs. @ 2600 RPM
Fuel Requirement	Unleaded Gasoline (87 Octane or higher)
Fuel Capacity	13.8 Gallons
Fuel Filter	Replaceable Automotive Type
Cooling System	Air-Cooled
Ignition	Electronic
Starter	12 Volt
Charging System	20 amp
DRIVE SYSTEM	
Transmission	Industrial Grade Dual Integrated Hydrostatic Transaxle
Pump Drive	Integrated Axial Piston Pump & Motor w/Planetary Gear Reduction
Wheel Drive	Hydro-Gear Integrated 4400 Series Transaxle
Hydrostatic System Oil	20W50 Motor Oil
Hydraulic Filter	Internal, Replaceable. 1 per axle
Pumps (2)	Hydro-Gear 12 cc Pump
Hydraulic Coolers (2)	9" 3600 RPM Cooling Fan: One per Unit
Weight	5400/1180 lbs /6100/1230 lbs.
Overall Height	48"
Overall Width	5400/55 1/2" / 6100/62 1/2"
Overall Length	86"
Tire to Tire Width	5400/52" / 6100/56"
Tires—Front	13 x 6.5–6 Smooth Tread
Tires—Rear	24x12-12 Turf Tread
Steering	Dual Lever Steering, Independent Control
Turning Radius	Zero Degree, Turns Within Unit Length
Ground Speed (forward)	Up to 11 mph
Parking Brake	Internal Wet Disk

SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at www.badboymowers.com. Not responsible for typographical errors. ©2017. Bad Boy, Inc., All Rights Reserved.