



# MOWER SPECIFICATIONS

## ZT ELITE MODELS

**KOHLER 725cc**

**KOHLER 747cc**

<b>Cutting Width</b>	<b>4800/48"</b>	<b>5400/54"; 6000/60"</b>
<b>Cutting Height</b>	1.5"–4.5" with Deck Height Control System	1.5"–4.5" with Deck Height Control System
<b>Blades</b>	<b>4800/1/4" x 2 1/2" x 16 1/2"</b> , High Lift, Heat Treated	<b>5400/1/4" x 2 1/2" x 18 3/4"</b> , High Lift, Heat Treated <b>6000/1/4" x 2 1/2" x 20 1/2"</b> , High Lift, Heat Treated
<b>Lift and Height Adjustment</b>	Instant Lift Electronic Actuator	Instant Lift Electronic Actuator
<b>Blade Belt</b>	Single V-Belt Spring Tension	Single V-Belt Spring Tension
<b>Anti-Scalp Rollers</b>	<b>4800/4</b> Total (2 On Front, 2 In Rear)	<b>5400/4</b> Total (2 Front, 2 Rear)/ <b>6000/6</b> Total (4 Front, 2 Rear)
<b>Deck Flotation</b>	Floats on (4) 1/4" Deck Hangers	Floats on (4) 1/4" Deck Hangers
<b>Deck Thickness</b>	3/16" Thick Solid Steel	3/16" Thick Solid Steel
<b>ENGINE</b>		
<b>Gross Horsepower</b>	725cc Air-Cooled Kohler Pro 7000	747cc Air-Cooled Kohler Pro 7000
<b>Cylinders</b>	90 Degree V-Twin	90 Degree V-Twin
<b>Displacement</b>	747 cc	747 cc
<b>Maximum Torque</b>	41.3 ft. lbs. @ 2400 RPM	41.3 ft. lbs. @ 2400 RPM
<b>Fuel Requirement</b>	Unleaded Gasoline (87 Octane or higher)	Unleaded Gasoline (87 Octane or higher)
<b>Fuel Capacity</b>	6.5 Gallons	6.5 Gallons
<b>Fuel Filter</b>	Replaceable In-Line Filter	Replaceable In-Line Filter
<b>Cooling System</b>	Air-Cooled	Air-Cooled
<b>Ignition</b>	Electronic	Electronic
<b>Starter</b>	12 Volt	12 Volt
<b>Charging System</b>	16 amp	16 amp
<b>DRIVE SYSTEM</b>		
<b>Transmission</b>	Hydro-Gear® 3100 Dual Integrated Hydrostatic Transaxle	Hydro-Gear® 3100 Dual Integrated Hydrostatic Transaxle
<b>Pump Drive</b>	Integrated Axial Piston Pump & Motor w/Gear Reduction	Integrated Axial Piston Pump & Motor w/Gear Reduction
<b>Wheel Drive</b>	Integrated with Commercial Grade Gear Reduction	Integrated with Commercial Grade Gear Reduction
<b>Hydrostatic System Oil</b>	20W50 Motor Oil	20W50 Motor Oil
<b>Hydraulic Filter</b>	25 Micron, Replaceable Spin-On Type, 1 Per Axle	25 Micron, Replaceable Spin-On Type, 1 Per Axle
<b>Pumps (2)</b>	10cc Pump and Motor Integrated in one unit	10cc Pump and Motor Integrated in one unit
<b>Hydraulic Coolers (2)</b>	7" Cooling Fan per Unit	7" Cooling Fan per Unit
<b>Weight</b>	<b>4800/783</b> lbs	<b>5400/823</b> lbs; <b>6000/838</b> lbs.
<b>Overall Height</b>	46"	46"
<b>Overall Width</b>	<b>4800/49 1/2"</b>	<b>5400/55 1/2"; 6000/61 1/2"</b>
<b>Overall Length</b>	77"	78"
<b>Tire to Tire Width</b>	46"	46"
<b>Tires—Front</b>	13 x 6.5–6 Smooth Tread	13 x 6.5–6 Smooth Tread
<b>Tires—Rear</b>	22 x 10–10 Turf Tread	22 x 10–10 Turf Tread
<b>Steering</b>	Dual Lever Steering, Independent Control	Dual Lever Steering, Independent Control
<b>Turning Radius</b>	Zero Degree, Turns Within Unit Length	Zero Degree, Turns Within Unit Length
<b>Ground Speed (forward)</b>	Up to 7 mph	Up to 7 mph
<b>Parking Brake</b>	Internal Parking Brake	Internal Parking Brake

**ANOTHER MODEL ON NEXT PAGE**

### SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at [www.badboymowers.com](http://www.badboymowers.com). Not responsible for typographical errors. ©2017. Bad Boy, Inc., All Rights Reserved.



# MOWER SPECIFICATIONS

## Kawasaki 726cc

<b>Cutting Width</b>	4800/48"; 5400/54"; 6000/60"
<b>Cutting Height</b>	1.5"–4.5" with Deck Height Control System
<b>Blades</b>	<b>4800</b> /1/4" x 2 1/2" x 16 1/2", High Lift, Heat Treated <b>5400</b> /1/4" x 2 1/2" x 18 3/4", High Lift, Heat Treated <b>6000</b> /1/4" x 2 1/2" x 20 1/2", High Lift, Heat Treated
<b>Lift and Height Adjustment</b>	Instant Lift Electronic Actuator
<b>Blade Belt</b>	Single V-Belt Spring Tension
<b>Anti-Scalp Rollers</b>	<b>4800</b> /4 Total (2 On Front, 2 In Rear) <b>5400</b> /4 Total (2 Front, 2 Rear)/ <b>6000</b> /6 Total (4 Front, 2 Rear)Floats on 2
<b>Deck Flotation</b>	Floats on (4) 1/4" Deck Hangers
<b>Deck Thickness</b>	3/16" Thick Solid Steel
<b>ENGINE</b>	
<b>Gross Horsepower</b>	726cc Air-Cooled Kawasaki FR
<b>Cylinders</b>	90 Degree V-Twin
<b>Displacement</b>	726 cc
<b>Maximum Torque</b>	40 ft. lbs. @ 2600 RPM
<b>Fuel Requirement</b>	Unleaded Gasoline (87 Octane or higher)
<b>Fuel Capacity</b>	6.5 Gallons
<b>Fuel Filter</b>	Replaceable In-Line Filter
<b>Cooling System</b>	Air-Cooled
<b>Ignition</b>	Electronic
<b>Starter</b>	12 Volt
<b>Charging System</b>	20 amp
<b>DRIVE SYSTEM</b>	
<b>Transmission</b>	Hydro-Gear® 3100 Dual Integrated Hydrostatic Transaxle
<b>Pump Drive</b>	Integrated Axial Piston Pump & Motor w/Gear Reduction
<b>Wheel Drive</b>	Integrated with Commercial Grade Gear Reduction
<b>Hydrostatic System Oil</b>	20W50 Motor Oil
<b>Hydraulic Filter</b>	25 Micron, Replaceable Spin-On Type, 1 Per Axle
<b>Pumps (2)</b>	10cc Pump and Motor Integrated in one unit
<b>Hydraulic Coolers (2)</b>	7" Cooling Fan per Unit
<b>Weight</b>	<b>4800</b> /788 lbs; <b>5400</b> /823 lbs; <b>6000</b> /841 lbs.
<b>Overall Height</b>	46"
<b>Overall Width</b>	<b>4800</b> /49 1/2"; <b>5400</b> /55 1/2"; <b>6000</b> /61 1/2"
<b>Overall Length</b>	74 1/2"
<b>Tire to Tire Width</b>	46"
<b>Tires—Front</b>	13 x 6.5–6 Smooth Tread
<b>Tires—Rear</b>	22 x 10–10 Turf Tread
<b>Steering</b>	Dual Lever Steering, Independent Control
<b>Turning Radius</b>	Zero Degree, Turns Within Unit Length
<b>Ground Speed (forward)</b>	Up to 7 mph
<b>Parking Brake</b>	Internal Parking Brake

### **SPECIFICATIONS ARE SUBJECT TO CHANGE.**

*We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at [www.badboymowers.com](http://www.badboymowers.com). Not responsible for typographical errors. ©2017. Bad Boy, Inc., All Rights Reserved.*